

**ONLEVEL** | Gap overview

GAP OVERVIEW													
ALUMINUM						STAINLESS STEEL							
2500MM		Maximum profile temperature					4000MM		Maximum profile temperature				
		40°C	50°C	60°C	70°C	80°C			40°C	50°C	60°C	70°C	80°C
Profile temperature during mounting	-20°C	4mm	4mm	5mm	5mm	6mm	Profile temperature during mounting	-20°C	4mm	5mm	6mm	6mm	7mm
	-10°C	3mm	4mm	4mm	5mm	5mm		-10°C	3mm	4mm	5mm	6mm	6mm
	0°C	3mm	3mm	4mm	4mm	5mm		0°C	3mm	4mm	4mm	5mm	6mm
	10°C	2mm	3mm	3mm	4mm	4mm		10°C	2mm	3mm	4mm	4mm	5mm
	20°C	1mm	2mm	3mm	3mm	4mm		20°C	2mm	2mm	3mm	4mm	4mm
	30°C	1mm	1mm	2mm	3mm	3mm		30°C	1mm	2mm	2mm	3mm	4mm
5000MM		Maximum profile temperature					6000MM		Maximum profile temperature				
		40°C	50°C	60°C	70°C	80°C			40°C	50°C	60°C	70°C	80°C
Profile temperature during mounting	-20°C	7mm	8mm	9mm	11mm	12mm	Profile temperature during mounting	-20°C	6mm	7mm	8mm	9mm	10mm
	-10°C	6mm	7mm	8mm	9mm	11mm		-10°C	5mm	6mm	7mm	8mm	9mm
	0°C	5mm	6mm	7mm	8mm	9mm		0°C	4mm	5mm	6mm	7mm	8mm
	10°C	4mm	5mm	6mm	7mm	8mm		10°C	3mm	4mm	5mm	6mm	7mm
	20°C	3mm	4mm	5mm	6mm	7mm		20°C	2mm	3mm	4mm	5mm	6mm
	30°C	1mm	3mm	4mm	5mm	6mm		30°C	1mm	2mm	3mm	4mm	5mm

